

# POWER CORE INDUSTRIES™

## BLANKING LAMINATION



DELIVERING YOUR DEMANDS

### Blanking Lamination

We manufacture all kinds of E&I laminations as per customer's specifications as well as Standard Types, which are used widely in CRGO grades M4, M5 and M6 and CRNGO Grades M45, M47, or as per customer's specified grade.

These type CRGO and CRNGO Transformer E&I Lamination are used in control transformer, Instrument

Transformers and Iron core chokes, Ballast and variety of electromagnetic application.

EI Dimension (in mm)										
SR NO	SIZE	A	B	C	D	E	F	G	H	I
1	1NO	28.6	22	4.76	4.76	9.53	4.76	4.76	28.6	
2	17NO	36.1	25.4	6.35	6.35	12.7	6.35	6.35	36.1	
3	17SPL	41.5	27.5	6.35	8	12.7	6.35	6.35	41.5	
4	12NO	48.1	31.75	8.02	8.02	16.04	8	8	48.1	
5	23NO	57.15	38.1	9.52	9.52	19.05				
6	30NO	60	40	10	10	20				
7	45NO	67.5	44.45	11.25	11.25	22.5				3
8	15NO	76.2	50.8	12.7	12.7	25.4	12.7	12.7	76.2	
9	33NO	94	56	14	14	28	14	14	84	6.75
10	3NO	96.25	63.5	16.04	32.06	16.04	16.04	96.25	6.75	
11	4 NO OR 16	114.3	76.2	19.05	19.05	38.1	19.05	19.05	114.3	6.75
12	6B	133.35	88.9	22.22	22.22	44.45	22.22	22.22	133.4	6.75
13	7NO OR 43	152.4	101.6	25.4	25.4	51.8	25.4	25.4	152.4	6.75
14	7B	190.5	127	31.75	31.75	63.5	31.75	31.75	190.5	8
15	8NO	184.15	146.05	25.4	41.5	50.8	25.4	25.4	184.2	8
16	8B	234.95	158.75	38.1	41.28	76.2	38.1	38.1	235	12
17	9 NO (9x12)	228.6	152.4	38.1	38.1	76.2	38.1	38.1	228.6	12.5
18	10 (10 1/2x14)	266.7	177.8	44.45	44.45	88.9	44.45	44.45	266.7	12.5
19	100NO(10x12)	304.8	203.2	50.8	50.8	101.6	50.8	50.8	304.8	12.5
20	200NO(12x16)	381	254	63.5	63.5	127	63.5	63.5	381	12.5

